



SN-NVR3704E1-P4

4CH 1HDD NVR with 4CH PoE



Key Features



- Up to 4ch IP cameras access
- Up to 1-ch @ 8MP or 4-ch @ 1080P decoding capacity
- VGA/HDMI simultaneous video output, maximum resolution of HDMI is 4K
- 1 SATA hard disk up to 8TB
- 1 RJ45 10M/100M network interface
- 4ch POE ports
- Smart search & playback
- Support cloud upgrade

Specification

Video Input	
IP Camera Input	4 Channel
Incoming Bandwidth	20 Mbps
Outgoing Bandwidth	20 Mbps
Video Output	
HDMI Output	3840×2160, 1920×1080, 1280×1024, 1024×768
VGA Output	1920×1080, 1280×1024, 1024×768
Decoding Capacity	1ch 4MP, 4ch 1080P@30fps
Dual Stream	Support
Multi-screen Display	1/4
Recoding	
Resolution	8MP, 6MP, 5MP, 4MP, 3MP, 1080P, 720P, D1 etc.
Recording Mode	Manual, Schedule (Regular, Continuous), Event
Trigger Events	Motion Detection, Video Loss, IVS
Playback and Backup	
Sync Playback	4/1
Search Mode	Time /Date, Alarm, Picture grid, Event
Backup Mode	USB Device, Network
Network	
Network Function	HTTP, HTTPS, TCP/IP, IPv4, UPnP, UDP, RTSP, SMTP, NTP, DNS, DHCP, P2P, IP Filter, DDNS, 802.1X, SNMP, 3G/4G, PPPoE
Remote Users	8 users
Smart Phone	iPhone, iPad, Android
Interoperability	ONVIF, SDK
Storage	
HDD	1 SATA interface
Capacity	Up to 8TB for each HDD

Interface	
Network Interface	1 RJ-45 (10/100 Mbps) self-adaptive Ethernet port
PoE	4 Ports (IEEE 802.3af), 24W
Audio I/O	1ch Audio output
USB	2 ports (USB 2.0 × 2)
HDMI	1
VGA	1
General	
Power Supply	DC48V/1.35A
Power Consumption	< 5 W (without HDD)
Operating Conditions	-10 °C ~ 50 °C (14 °F ~ 122 °F)
Storage Conditions	Less than 90% RH
Certifications	CE/FCC
Dimensions	255 × 237 × 47.5 mm (10.04 × 9.33 × 1.87 inch)
Net Weight	0.9 kg (1.98 lb) without HDD

Dimensions (mm)



Rear Panel

